

25 TON AIR-COOLED CHILLER



PA-ACCTR-25

The 25-Ton portable chiller package features a Trane® CGAM chiller unit. Trane® leads the industry in providing some of the most reliable, efficient and quiet chiller units in the marketplace. Trane® CGAM chiller units feature direct-drive, low-speed scroll compressors, microprocessor control systems, factory installed strainer systems and flow switches. All of these features are key components to keeping your chiller system operating for the long haul.

All portable chiller units are mounted on Heavy-Duty and DOT Approved trailer designs with plenty of storage for chiller accessories that you can count on to last. Trailers are constructed using an all-steel frame with wood decking material with brake options to include: electric, hydraulic or pneumatic packages.



Call us today! (800)341-4297



GENERAL

◆ Trane® Chiller Model	CGAM026F2
◆ CFM (Cubic Feet Per Minute)	18897
◆ Number of fans	2
◆ Number of compressors	2

DIMENSIONS

◆ Length with Trailer	234"
◆ Width with Trailer	76"
◆ Height with Trailer	117"
◆ Shipping Weight with Trailer	4,580 Pounds

ELECTRICAL DATA

◆ Power Supply	460V/3PH/70A/60Hz
◆ Water Connections	4" Camlock
◆ Minimum Circuit Ampacity	56.4A
◆ Min/Max Operational Volts	414V - 506V

ADDITIONAL INFORMATION

- ◆ Architectural Louvered Panels

25 TON AIR-COOLED CHILLER FEATURES

- ◆ Single Point Power Connection with Quick Connect Camlock Connections
- ◆ Integrated Circuit Breaker Overcurrent Protection
- ◆ 2 HP/60 GPM Pump Package
- ◆ (2) 50' Suction/Discharge Water Hoses
- ◆ 100' #2 AWG Power Cable with Camlock Connectors

25 TON AIR-COOLED CHILLER



Product Data - Air-Cooled Scroll All Units

Air-Cooled Scroll Packaged Chiller
60 hertz
460 volt 3 phases
High efficiency/performance
Full factory refrigerant charge (HFC-410A)
With freeze protection (External T-STAT control)
Refrigerant isolation valves (discharge valve)
UL listed
ASHRAE 90.1 all versions compliant
AHRI certified
Factory installed flow switch - set point 65 cm/sec
Standard cooling (42 to 65F/5.5 to 18C)

Grooved pipe connection
Factory insulation - all cold parts
Performance based on water
Wide ambient (0 to 125F/-18 to 52C)
Lanced aluminum fins
Across the line starter/direct on line
Single point power connection
Circuit breaker-high fault rated control panel
Enclosure type UL 1995 rated for outdoor applications
High A short circuit rating
With water strainer factory installed
Super quiet
Architectural louvered panels

Performance Data - Air-Cooled Scroll

Tags	25 Ton	Tags	25 Ton
Capacity (tons)	24.6	Saturated cond temp circuit 1 (F)	124.10
Unit power input (kW)	30.00	Saturated cond temp circuit 2 (F)	-
Full load efficiency (EER)	9.8	Compressor power input (kW)	27.4
NPLV (EER) 1	14.8	RLA - compressor 1A (A)	21.20
IPLV (EER)	15.1	LRA - compressor 1A (A)	158.00
Sound power level (dBA)	86	RLA - compressor 1B (A)	21.20
Sound pressure level (dBA)	61	LRA - compressor 1B (A)	158.00
Refrigerant	R410A	RLA - compressor 2A (A)	-
Refrigerant charge circuit 1 (lb)	34.0	LRA - compressor 2A (A)	-
Refrigerant charge circuit 2 (lb)	-	RLA - compressor 2B (A)	-
Oil charge circuit 1 (gal)	1.74	LRA - compressor 2B (A)	-
Oil charge circuit 2 (gal)	-	Total airflow (cfm)	18897
Evap entering temp (F)	56.00	Number of fans ()	2
Evap leaving temp (F)	42.00	Fan motor power (kW)	2.40
Evap flow rate (gpm)	42.00	Total fan FLA (A) 2	6.90
Min evap flow rate (gpm)	37.20	Single point power MCA (A)	56.40
Min flow PD evap+strainer (ft H2O)	5.30	Single point power MOP (A)	70.00
Max evap flow rate (gpm)	89.40	Short circuit current rating (A)	65000.00
Max flow PD evap+strainer (ft H2O)	28.50	Number of compressors ()	2
Evap fluid freeze point (F)	32.00	Number of circuits ()	1
Evap press drop (ft H2O)	5.90	Capacity steps ()	2
Total PD evap+strainer (ft H2O)	6.60	Shipping weight (lb)	2249.4
Evap fouling factor (hr-sq ft-deg F/Btu)	0.00010	Operating weight (lb)	2278.5
Saturated evap temp circuit 1 (F)	36.70	Length (in)	114.000
Saturated evap temp circuit 2 (F)	-	Width (in)	50.600
Ambient air temperature (F)	95.00	Height (in)	84.700
Elevation (ft)	0.00		